

STARTING PROBLEMS?

550.1850

**12 V / 24 V
CAPACITOR BOOSTER —
MOBILE EMERGENCY STARTER
4700 A / 3700 A**



550.1725



550.1825



550.1820



550.1720



K20

PREMIUM-WERKZEUGE

KSTOOLS

PREMIUM TOOLS



550.1850

**12 V / 24 V CAPACITOR BOOSTER –
 MOBILE EMERGENCY STARTER 4700 A / 3700 A**

- Based on super capacitor technology
- Maintenance-free
- Ideal for petrol and diesel engines in cars through to transporters
- Integrated electronics protection
- Acoustic and optical warning tone if the polarity is reversed



Technical data:

Capacitor: 12 Volt / 24 Volt / 3400 FARAD
 Peak current: 20.000/10.000 A
 Starting current: 4700/3700 A

1998,⁹⁰ €

550.1725

**12 V + 24 V BATTERY BOOSTER -
 MOBILE STARTING AID 3000 A**

- Ideal for petrol and diesel engines in cars through to transporters
- Integral electronics protection (voltage peak protected)
- Intelligent, fully-integrated 3-stage automatic charging unit
- Polarity protection optical/acoustic
- Robust, wheeled housing with cable storage compartments



Technical data:

Battery: 2 x 12 Volt / 50 Ah
 Peak current: 7200 / 3400 A
 Starting current: 3000 / 1500 A

1918,⁵⁰ €

550.1825

**12 V + 24 V BATTERY BOOSTER -
 MOBILE EMERGENCY STARTER 2340 A**

- Ideal for petrol and diesel engines in cars through to transporters
- Integrated electronics protection
- Acoustic warning tone if the polarity is reversed
- Current-free cable connection to the vehicle battery
- Robust, wheeled housing with cable storage compartments



Technical data:

Battery: 2 x 12 Volt / 25 Ah
 Peak current: 6200/3100 A
 Starting current: 2340/1170 A

1453,⁵⁰ €

550.1820

**12 V + 24 V BATTERY BOOSTER -
 MOBILE STARTING AID 1700 A**

- Ideal for petrol and diesel engines in cars through to transporters
- Integrated electronics protection
- Acoustic warning tone if the polarity is reversed
- Current-free cable connection to the vehicle battery
- Battery charger, cable set and safety fuse included in the delivery



Technical data:

Battery: 2 x 12 Volt / 22 Ah
 Peak current: 5000/2500 A
 Starting current: 1700/850 A

1001,⁵⁰ €

550.1720

**12 V + 24 V BATTERY BOOSTER -
 MOBILE STARTING AID 1400 A**

- Ideal for petrol and diesel engines in cars through to transporters
- Fully insulated terminal clamps (1000 A)
- Acoustic warning tone if the polarity is reversed
- Current-free cable connection to the vehicle battery
- Impact-resistant housing with rubberised base area



Technical data:

Battery: 2 x 12 Volt / 22 Ah
 Peak current: 4400 / 2200 A
 Starting current: 1400 / 700 A

599,⁹⁰ €

550.1649

**12V / 24V BATTERY-, CHARGING-
 AND STARTING SYSTEM ANALYZER
 WITH INTEGRATED PRINTER**

- Suitable for 12 volt batteries (lead acid, gel, wet cell, MF, VRLA, calcium, AGM and deep cycle batteries)
- For the quick and simple determination of battery efficiency while taking the temperature compensation into account
- Checks the battery condition, charge status, internal resistance, cold start current value
- With verification function for the starter battery, starter and load circuit measurement
- Avoidance of an overload of the battery through too long of a measurement time



Technical data:

Readout: digital
 Work area CA / MCA: 40-2.000 CCA
 Work area CCA: 40-2.000 CCA
 Work area DIN: 40-2.000 CCA
 Work area EN: 40-2.000 CCA
 Work area IEC: 40-2.000 CCA
 Work area JIS#: 40-2.000 CCA
 Work area SAE: 40-2.000 CCA
 Operating temperature: +0°C to +55°C
 Frequency range: 100 Hz
 Working range: 9-36 V
 Display accuracy: +/- 0,5 Megaohm



367,⁹⁰ €